

MANNINGTON COMMERCIAL.

Mannington Edge™ Wall Base

Construction	Thermoplastic vinyl, Type TV
Finish	Matte Finish
Height / Size	2 ½ " (63.5 mm) 4 " (101.6 mm) 6 " (152.4 mm) Coved or Toeless
Corners	Factory Pre-formed, specify jobsite wrapped or pre-formed
Overall Thickness	.080 inches (2.032 mm) & 1/8 "(3.175 mm)
Pieces per Carton	1-100' continuous roll or 25 – 4' pieces
Weight per Carton – (2 ½" / 4" / 6")Coved (.080")	= 19 / 27 / 42 lbs Toeless (.080") = 17 / 25 / 39 lbs Coved (1/8") = 24 / 37 / 53 lbs Toeless (1/8") = 23 / 36 / 52 lbs
Weight per Carton – (Corners)	Coved (.080") = 3 / 3 / 8 lbs Toeless (.080") = 2 / 3 / 7 lbs Coved (1/8") = 3 / 4 / 9 lbs Toeless (1/8") = 3 / 4 / 9 lb
ASTM Specification (F-1861)	Type TV, Group 1
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm², Passes (Class I)
N.B.S. Smoke chamber Test (ASTM-E-662)	<450 - Passes
Installation Adhesive	Mannington MR-101 Acrylic Wall Base Adhesive
Warranty	Limited Five Year Commercial Warranty

Mannington Edge Wall Base Collection is not recommended in commercial areas that require static dissipation. Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Protect all materials from the direct flow of heat from hot-air registers, radiators, or other heating fixtures and appliances.

Dirt, wetness, and improper maintenance may cause significant variation in actual performance. Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance. This product is intended solely for use indoors and is not recommended or sold for any other purpose.